





MULTI-RANGE DIGITAL TIMER

多段式數位型限時繼電器

SPECIFICATION 規格		AH3D-M	AH3D-DM	AH4D-DM	BH3D-DM
Model 型號					
Dimension(mm) 尺寸		50H*40W*57.5D		48H*48W*84D	48H*48W*53D
Time Range 時間範圍		x.01Sec, x0.1Sec, x1Sec, x.59Sec x0.1Min, x1Min, x.59Min x0.1Hr, x1Hr, x10Hr			
Supply Voltage 額定電壓		DC(V): 12, 24 AC(V): 12, 24, 48, 110, 220, 240 380, 415, 440, 50/60Hz			
Contact Rating 接點容量		250VAC 5A Resistive Load 48VDC 5A 電阻性負載			
Reset Time 複歸時間		0.1 sec max			
Consumed Power 消耗功率		3VA			
Ambient Temperature 使用周圍溫度		-10℃~ +55℃			
Ambient Humidity 使用周圍濕度		45~85%RH			
Life 壽命	Mechanical 機械	5×10 ⁶ times			
	Electrical 電氣	10 ⁵ times			
Weight 重量		130g		150g	136g
Connection 接線圖		限時2C  mode A 限時1C, 瞬時1C  mode B			
Timing Chart 時序圖		 Rt:Resetting time  Rt:Resetting time			