



DIGITAL TWIN TIMER 數位型雙調型限時繼電器

SPECIFICATION 規格		TDV-NM	TDV-YM	TDV-NDM	TDV-YDM
Model 型號					
Dimension(mm) 尺寸		61H*49W*70D	88H*58W*68D	61H*49W*70D	88H*58W*68D
Time Range 時間範圍		x.01Sec, x0.1Sec, x1Sec, x.59Sec x0.1Min, x1Min, x.59Min x0.1Hr, x1Hr, x10Hr			
Supply Voltage 額定電壓		DC(V): 12, 24 AC(V): 12, 24, 48, 110, 220, 240 380, 415, 440, 50/60Hz			
Contact Rating 接點容量		250VAC 5A Resistive Load 48VDC 5A 電阻性負載			
Reset Time 複歸時間		0.1 sec max			
Consumed Power 消耗功率		3VA			
Ambient Temperature 使用周圍溫度		-10°C~+55°C			
Ambient Humidity 使用周圍濕度		45~85%RH			
Life 壽命	Mechanical 機械	5×10 ⁶ times			
	Electrical 電氣	10 ⁵ times			
Weight 重量		210g			
Connection 接線圖		限時2C  mode A			
Timing Chart 時序圖		限時1C, 瞬時1C  mode B POWER (2-7) OFF NC (8-5) ON NO (8-6) OFF NC (1-4) ON NO (1-3) OFF LAMP ON LAMP POWER (2-7) OFF NC (8-5) ON NO (8-6) NC (1-4) NO (1-3) OFF LAMP ON LAMP			